





Tube Fabrication Notes:

- Material is mild steel tube, 1.25" outside diameter by .065" wall thickness or similar.
- Ņ All bends are 90 degrees unless otherwise noted. All bend radii may be any dimension between 4 and 5 inches centerline radius.
- $\dot{\sigma}$ All notching is for 1 5/8" (1 1/2" - 1 3/4" is acceptable) tube diameter.
- 4. Most dimensions are non-critical and a plus or minus tolerance of as much as .I" is acceptable. Critical dimensions requiring as tight a tolerance as reasonably possible (.03" \pm or better) will be indicated with an asterisk (*).

_	_	_	_
	Re√.	Œ	
		Reduced fork width to 3.86" to correct previous mistake.	
,		oth to 3.86"	
3	Description	to correct	
1	tion	previou	
:		s mistak	
The state of the s		€.	
Draw			
à by: K.⊏	Date	1/17/2013 KLN	
Nikolich	Ву	KLN	
			_

- 1						
	(was formerly HWI-DOTTCC-T-017)	Drawing No. $HWI-DOTTU-T-017$		Early Arm Take	Used On Both Standard & Compact Versions	
	-Part Number 017		Sheet no. 1 0f 1	Scale: None	Date: April 4	= · = · · · · · · · · · · · · · · · · ·

7TTI]-T-017	ke (DOTT-B & C) Compact Versions				
	Sheet no. 1 0f 1	Scale: None	Date:		
	o. 1 Of 1	Vone	April 4		
REV.			April 4, 2012		

 $|_{\varpi}$