

Tube Fabrication Notes:

- 1. Material is mild steel tube, 1.25" outside diameter by .065" wall thickness or similar.
- ? All bends are 90 degrees unless otherwise noted. All bend radii may be any dimension between 4 and 5 inches centerline radius.
- All notching is for 1 1/4" tube diameter, unless otherwise noted.
- 4. Most dimensions are non-critical and a plus or minus tolerance of as much as .1" is acceptable. Critical dimensions requiring as tight a tolerance as reasonably possible (.03" \pm or better) will be indicated with an asterisk (*).

		Rev.	
HWI Dual Offset Tube Trike (DOTT)		Description	
	Drawn by: K.L.Nikolich		
		Date	
		Ву	
	-		

Drawing No. $HWI ext{-}DOTTCC ext{-}T ext{-}010$ $HWI ext{-}$ Dual Offset Tube Trike Version C, Compact-Trike part Part Number 010	Leg Rest Ankle Support Tube	Compact Version	Command Provider	HWI Dual Offset Tube Trike (DOTT)	Descripaci
010rike part -Part Number 010	Sheet no. 1 0f 1	Scale: None	Date: April 4, 2012	Drawn by: K.L.Nikolich	Date
₩.	1		. 4, 2012	Nikolich	L)